Fig. 200R (Screwed), 201R (Flanged) Cast Iron HNH-Milliken Plug Valves - Round Port, Full Bore

FEATURES & BENEFITS

- Sealing compound effects a completely leak tight seal
- When open presents a straight through passage in line with pipeline
- Stops flow after 90° turn
- Unless requested plug valves will be supplied with the standard compound No.90



DIMENSIONAL DRAWINGS




Fig. 200R - Sizes 1", 11/2" and 2" only




Fig. 201R - Sizes 11/4" to 4" 4" size has bolted bottom cover

Every effort has been made to ensure that the information contained in this publication is accurate at the time of publishing. Hattersley Ltd assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the

DIMENSIONS & WEIGHTS

Dimensions 200R and 201R

mm in	25 1	32 1 ¹ /4	40 1 ¹ /2	50 2	65 2 ¹ /2	80 3	100 4
mm	106	-	140	190	-	-	-
mm	-	127	133	190	222	244	324
in	5	5 ¹ /4	7 ¹ /2	83/4	9 ⁵ /8	12 ³ /4	
mm	114	124	140	206	216	245	286
in	41/4	4 ⁵ /8	5	6	7	71/2	9
	J	J	L	0	0	Р	Q
kg	1.9	3.6	4.9	12	19	25	60
kg	3.8	5.8	7.5	17	23	30	61
	in mm mm in kg	in 1 106 mm 106 mm - in 5 mm 114 in 41/4 J kg 1.9	in 1 11/4 mm 106 - mm - 127 in 5 51/4 mm 114 124 in 41/4 45/8 J J kg 1.9 3.6	in 1 11/4 11/2 mm 106 - 140 mm - 127 133 in 5 51/4 71/2 mm 114 124 140 in 41/4 45/8 5 J J L kg 1.9 3.6 4.9	in 1 11/4 11/2 2 mm 106 - 140 190 mm - 127 133 190 in 5 51/4 71/2 83/4 mm 114 124 140 206 in 41/4 45/8 5 6 J J L O kg 1.9 3.6 4.9 12	in 1 11/4 11/2 2 21/2 mm 106 - 140 190 - mm - 127 133 190 222 in 5 51/4 71/2 83/4 95/8 mm 114 124 140 206 216 in 41/4 45/8 5 6 7 J J L O O kg 1.9 3.6 4.9 12 19	in 1 11/4 11/2 2 21/2 3 mm 106 - 140 190 - - - mm - 127 133 190 222 244 in 5 51/4 71/2 83/4 95/8 123/4 mm 114 124 140 206 216 245 in 41/4 45/8 5 6 7 71/2 J J L O O P kg 1.9 3.6 4.9 12 19 25